

CLAIMS AMENDMENTS

CLAIMS

1. (Original) A method for allowing a Mobile IPv4 Mobile Node to communicate from an IPv6 visited network, and across IPv6 networks, back to a Mobile IPv4 Home Agent, in a Mobile IPv4 Network, comprising:
 - a Mobile Node supporting Mobile IPv4 registration procedures including IPv6 addressing details to support MN – HA communication;
 - a Home Agent supporting connectivity to both IPv4 and IPv6 networks to facilitate remote access;
 - tunneling of IPv4 traffic over IPv6 networks from the Mobile Node;
 - tunneling of Mobile IPv4 traffic over IPv6 networks from the Home Agent.
2. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 1, wherein the Mobile Node acquires an IPv6 address in the visited network.
3. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 2 wherein the Mobile Node sends a MIPv4 Registration Request over IPv6 using the acquired IPv6 address as source address, and the Home Agent IPv6 address as destination address.
4. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 2, wherein the Mobile Node includes the acquired IPv6 address as an IPv6 care-of address extension in the Mobile IPv4 Registration Request.
5. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 1, wherein the Home Agent extracts the IPv6 care-of address from the Registration Request extension and uses it as the tunnel endpoint for the IPv4 in IPv6 tunnel back to the Mobile Node.

6. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 1, wherein the Mobile Node tunnels IPv4 packets in IPv6 headers, destined for the Home Agent.
7. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 1, wherein the Mobile Node de-capsulates IPv6 tunneled IPv4 packets from the Home Agent.
8. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 1, wherein the Home Agent accepts Mobile IPv4 Registration Requests arriving on an IPv6 network.
9. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 1, wherein the Home Agent tunnels IPv4 packets in IPv6 headers, destined for the Mobile Node.
10. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 1, wherein the Home Agent de-capsulates IPv6 tunneled IPv4 packets from the Mobile Node.
11. (Currently Amended) ~~A~~The method ~~according to~~of ~~e~~Claim 1, wherein the Home Agent employs UDP tunneling from the HA to the MN in accordance with RFC 3519.